

Linoleum

		Veneto xf ^{2™} 2 mm	Veneto xf ^{2™} , Style Emme xf ^{2™} , Style Elle xf ^{2™} , Etrusco xf ² , Trentino xf ^{2™} , Originale xf ² 2.5 mm	Linoleum xf ^{2™} Bfl 2.5 mm	Originale Essenza, Veneto Essenza 2.5 mm
ISO 24011 (EN 548)					
EN 686	-	-	-	-	-
EN 687	-	-	-	-	-
EN 14041					
	23/32/41	23/34/43	23/34/43	23/34/43	23/34/43
	xf ^{2™}	xf ^{2™}	xf ^{2™}	Essenza	
EN ISO 24346	2.0 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm
EN ISO 23997	ca. 2 400 g/m ²	ca. 3 000 g/m ²	ca. 3 200 g/m ²	ca. 3 000 g/m ²	ca. 3 000 g/m ²
EN ISO 24343-1	≤ 0.15 mm ca. 0.07 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm
EN ISO 24344	≤ 25 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø
EN ISO 24341	≤ 32 x 2 m	≤ 32 x 2 m	≤ 16 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m
EN 13501-1	Cfl-s1	Cfl-s1	Bfl-s1	Cfl-s1	
ISO 5659-2	-	-	-	-	
EN ISO 10140-3 / EN ISO 717-2	5 dB	6 dB	5 dB	6 dB	
NF S31-074	C < 85 dB	C < 85 dB	C < 85 dB	C < 85 dB	
EN ISO 10140-3 EN ISO 717-2	14 dB	14 dB	14 dB	14 dB	
EN ISO 4918					
EN 1815	< 2 kV	< 2 kV	< 2 kV	< 2 kV	
EN 1081	-	-	-	-	
	-	-	-	-	
	-	-	-	-	
EN 259-2	-	-	-	-	
EN 13893 DIN 51130	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	
EN ISO 26987					
EN ISO 10456	0.012 m ² K/W	0.015 m ² K/W	0.015 m ² K/W	0.015 m ² K/W	
EN ISO 105-B02	≥ 6	≥ 6	≥ 6	≥ 6	
CEN ISO/TS 16181					
EN ISO 16000-28 i.A., VDI 4302					
EN 12956 EN 233	-	-	-	-	
ISO 22196					
	19	60 (Veneto) / 13 (Style Emme) / 8 (Style Elle) / 16 (Etrusco) / 10 (Trentino) 3 (Originale Vegetale) / 3 (Originale Minerale)	60 (Veneto Bfl) / 13 (Style Emme Bfl) / 8 (Style Elle Bfl) / 16 (Etrusco Bfl) / 10 (Trentino Bfl)	29 (Veneto) / 3 (Originale Vegetale) / 3 (Originale Minerale)	

Linoleum

Veneto Sicuro xf ² ™ R10 2.5 mm	Linoleum Conductive xf ² ™ 2.5 mm	Linoleum SD Static Dissipative xf ² ™ 2.5 mm	Veneto xf ² ™ 3.2 mm	Silencio xf ² ™ 3.8 mm - 19 dB	Veneto Acoustic Cork xf ² ™ 4.4 mm - 15 dB	LinoWall 2 mm
-	-	-	-	-	-	-
-	-	-	-	-	-	-
23/34/43	23/34/43	23/34/43	23/34/43	23/33/41	23/34/42	-
xf ² ™	xf ² ™	xf ² ™	xf ² ™	xf ² ™	xf ² ™	xf ² ™
2.5 mm	2.5 mm	2.5 mm	3.2 mm	3.8 mm	4.4 mm	2.0 mm
ca. 3 000 g/m ²	ca. 3 000 g/m ²	ca. 3 000 g/m ²	ca. 3 900 g/m ²	ca. 3 450 g/m ²	ca. 4 600 g/m ²	ca. 2 900 g/m ²
≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.10 mm	≤ 0.30 mm ca. 0.20 mm	≤ 0.40 mm ca. 0.25 mm	-
≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 40 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	-
≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m or ≤ 32 x 1.95 m		≤ 16 x 2 m /
Cfl-s1	Bfl-s1	Cfl-s1	Cfl-s1	Cfl-s1	Cfl-s1	B-s2 d0
-	-	-	-	-	-	-
6 dB	6 dB	6 dB	8 dB	19 dB	15 dB	-
C < 85 dB	C < 85 dB	C < 85 dB	B < 75 dB	A < 65 dB	B < 75 dB	-
14 dB			15 dB			-
< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV
-	R1 ≤ 10 ⁶ Ω	R1 ≤ 10 ⁸ Ω	-	-	-	-
-	R2 ≤ 10 ⁶ Ω	R2 ≤ 10 ⁸ Ω	-	-	-	-
-	R ≤ 10 ⁶ Ω	1x10 ⁶ < R < 1x10 ⁸ Ω	-	-	-	-
-	R ≤ 10 ⁶ Ω	R ≤ 10 ⁸ Ω	-	-	-	-
DS: ≥ 0.30 R10	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	-
0.015 m ² K/W	0.015 m ² K/W	0.015 m ² K/W	0.019 m ² K/W	0.042 m ² K/W	0.045 m ² K/W	0.018 m ² K/W
≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6
-	-	-	-	-	-	-
60 (Veneto)	16	3	9	27 (Veneto) / 8 (Style Emme) / 1 (Style Elle) / 3 (Etrusco) 10 (Trentino)	60 (Veneto)	6

Linoleum



Acoustic Cork	93 % 77 % Natural Renewable	100 % 33 % Recyclable Recycled content	PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS
Etrusco	93 % 77 % Natural Renewable	100 % 34 % Recyclable Recycled content	PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS
SD (Static Dissipative)	98 % 58 % Natural Renewable	100 % 18 % Recyclable Recycled content	PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS
Trentino	94 % 76 % Natural Renewable	100 % 36 % Recyclable Recycled content	PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS

Conductive	96 % 58 % Natural Renewable	100 % 18 % Recyclable Recycled content	PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS
LinoWall			PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS
Silencio	83 % 65 % Natural Renewable	100 % 40 % Recyclable Recycled content	PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS
Veneto	94 % 76 % Natural Renewable	100 % 36 % Recyclable Recycled content	PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS

Elafono (underlayer)	100 % 85 % Natural Renewable	100 % 34 % Recyclable Recycled content	PHthalate FREE	≤100 µg/m³ Better Indoor Air Quality *TVOC AT 28 DAYS
Originale	99 % 80 % Natural Renewable	100 % 30 % Recyclable Recycled content	PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS
Style	96 % 74 % Natural Renewable	100 % 30 % Recyclable Recycled content	PHthalate FREE	≤10 µg/m³ Optimal Indoor Air Quality *TVOC AT 28 DAYS



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

